

# Ecoflo<sup>®</sup> Coco Filter

## Septic System

Polyethylene • Ready-to-use

20  
year  
WITH YOU



## WASTEWATER TREATMENT

Light, robust and easy-to-handle for a variety of machinery, the award-winning Ecoflo<sup>®</sup> Biofilter Ready-to-Use is delivered to sites entirely pre-assembled and ready to be installed.

## NEW MODEL FOR ILLINOIS!

**More durable filtering media**

**More compact and  
economical than ever**

**Permanent and  
environmentally-friendly**

**Long-lasting coco filtering media!**

Made of 100% natural, highly porous coconut fragments – an ideal material for treating wastewater with the added benefit of dramatically reducing tank size.

At the end of its useful life (up to 15 years), the used filtering media is simply removed and replaced via the cover of the biofilter and its 8-year warranty is automatically renewed.

Ecoflo<sup>®</sup> Coco Filter is also available in concrete tanks made in the USA by local precasters to further reduce the carbon footprint of the product.

# The success and proven reliability of Ecoflo® Biofilter

Our 20 years of Innovation, Research and Development have resulted in the highest performance, most flexible and reliable onsite wastewater treatment system for homeowners, small communities and small businesses.

Extensively tested in both North America and Europe by third-party entities, Ecoflo has proven to be the very best.

**Unparalleled maintenance program provided by an extensive network of local service partners.**


**100,000  
SYSTEMS INSTALLED!**



**Try our new models!**

**Ecoflo®** *Coco Filter*

Polyethylene



MODELS	ECP-750/G-USA	ECP-750/P-USA	ECP-970/G-USA	ECP-970/P-USA
<b>Nb of bedrooms</b>	Up to 5 bedrooms		Up to 6 bedrooms	
<b>Type of disposal</b>	gravity	pumped	gravity	pumped
<b>Filter area</b>	61 ft² (5.7 m²)		78.5 ft² (7.3 m²)	
<b>Length</b>	10' 5" (3,180 mm)		13' 9" (4,200 mm)	
<b>Width</b>	6' 7" (2,000 mm)		6' 9" (2,050 mm)	
<b>Height</b>	6' 1" (1,850 mm)		6' 1" (1,850 mm)	
<b>Intlet height</b>	4' 2" (1,260 mm)		4' 2" (1,260 mm)	
<b>Outlet height</b>	1 1/2" (38 mm)	4' 1" (1,240 mm)	1 1/2" (38 mm)	4' 1" (1,240 mm)
<b>Weight*</b> (including internal components and filtering media)	2,620 lb (1,190 kg)	2,640 lb (1,200 kg)	3,100 lb (1,405 kg)	3,120 lb (1,415 kg)
<b>Dosing volume</b>	—	38 US gal (145 L)	—	48 US gal (180 L)
<b>Retention volume</b> (between bottom of tank and under the filtering media)	—	130 US gal (500 L)	—	190 US gal (715 L)

\*Weights indicated are approximate and not binding. For handling and lifting purposes only.

## Disposal Options

- A** Ecoflo® Coco Filter Polyethylene with watertight bottom discharged by gravity (ECP-750/G-USA and ECP-970/G-USA)
- B** Ecoflo® Coco Filter Polyethylene with watertight bottom and integrated pump (ECP-750/P-USA and ECP-970/P-USA)

**The longest septic installation warranty available on the market!**

Available at:



**Zeiter's Septics Unlimited, Inc.**

2400 N Route 47

Morris, IL, 60450

☎ 815 942-2829 | [zeiterseptic.com](http://zeiterseptic.com)



1 800 632-6356  
[ECOFLOBIOFILTER.COM](http://ECOFLOBIOFILTER.COM)



The information contained in this document is based upon the latest information available at the time of publication and is designed to provide you with a general introduction to our products. We make no warranties or representations as to its accuracy. We are continually updating and improving our products and reserve the right to amend, discontinue, alter or change specifications and prices without prior notice. Ecoflo® is a brand of Premier Tech Ltd. The Ecoflo® Coco Filter is protected under patents: CA2149202; CA2499637; US5618414; US7097768; ES2131396; ES2285173; EP0836585 (in BE, CH, FR, GB, IE, IT, LI, NL); EP1539325 (in BE, FR). Notice issued on 2014-08-19. For current data regarding all patent application(s) and patent(s) for this product or any part thereof, consult the website [patentmarking.premiertech.com](http://patentmarking.premiertech.com) (references: 8367, 3685).

© Premier Tech Ltd, 2015

